

IW6-3MR

Woofer:	6.5"fiber Glass Cone
Tweeter:	1"SILK DOME
Impedance:	8Ω
Sensitivity:	90dB
Frequency Response:	50Hz - 20kHz
Rated Power:	50 Watts
Cutout Diameter:	27.6" * 7.96"

Dyatt Audio Co., Ltd

Out Speaker



OW-425

Woofer:	4"kevlar Cone
Tweeter:	1" ALuminum DOME
Impedance:	8Ω
Sensitivity:	86dB
Frequency Response:	90Hz - 20kHz
Rated Power:	25 Watts
Cutout Diameter:	/



OW-525

Woofer:	51/4"kevlar Cone
Tweeter:	1" ALuminum DOME
Impedance:	8Ω
Sensitivity:	87dB
Frequency Response:	80Hz - 20kHz
Rated Power:	25 Watts
Cutout Diameter:	/



OW-625

Woofer:	6.5"kevlar Cone
Tweeter:	1" ALuminum DOME
Impedance:	8Ω
Sensitivity:	88dB
Frequency Response:	70Hz - 20kHz
Rated Power:	30 Watts
Cutout Diameter:	/



OD-425A

Woofer:	4"Injection Cone
Tweeter:	1" ALuminum DOME
Impedance:	8Ω
Sensitivity:	86dB
Frequency Response:	90Hz - 20kHz
Rated Power:	25 Watts
Cutout Diameter:	/



OD-525A

Woofer:	51/4"Injection Cone
Tweeter:	1" ALuminum DOME
Impedance:	8Ω
Sensitivity:	87dB
Frequency Response:	80Hz - 20kHz
Rated Power:	25 Watts
Cutout Diameter:	/



OD-625A

Woofer:	6.5"Injection Cone
Tweeter:	1" ALuminum DOME
Impedance:	8Ω
Sensitivity:	88dB
Frequency Response:	70Hz - 20kHz
Rated Power:	30 Watts
Cutout Diameter:	/



OH-425

Woofer:	4"PP Cone
Tweeter:	1" Silk DOME
Impedance:	8Ω
Sensitivity:	86dB
Frequency Response:	90Hz - 20kHz
Rated Power:	25 Watts
Cutout Diameter:	/



OH-525

Woofer:	51/4"PP Cone
Tweeter:	1" Silk DOME
Impedance:	8Ω
Sensitivity:	87dB
Frequency Response:	80Hz - 20kHz
Rated Power:	25 Watts
Cutout Diameter:	/



OH-625

Woofer:	6.5"PP Cone
Tweeter:	1" Silk DOME
Impedance:	8Ω
Sensitivity:	88dB
Frequency Response:	70Hz - 20kHz
Rated Power:	30 Watts
Cutout Diameter:	/



OT-425

Woofer:	4"Fiber Glass Cone
Tweeter:	0.5" PEI DOME
Impedance:	8Ω
Sensitivity:	86dB
Frequency Response:	90Hz - 20kHz
Rated Power:	25 Watts
Cutout Diameter:	/



OT-525

Woofer:	51/4"Fiber Glass Cone
Tweeter:	0.75" PEI DOME
Impedance:	8Ω
Sensitivity:	87dB
Frequency Response:	80Hz - 20kHz
Rated Power:	25 Watts
Cutout Diameter:	/



OT-625

Woofer:	6.5"Fiber Glass Cone
Tweeter:	1" PEI DOME
Impedance:	8Ω
Sensitivity:	88dB
Frequency Response:	70Hz - 20kHz
Rated Power:	30 Watts
Cutout Diameter:	/



SD-425

Woofer:	4"Injection Cone
Tweeter:	1" ALuminum DOME
Impedance:	8Ω
Sensitivity:	86dB
Frequency Response:	90HZ--20K HZ
Rated Power:	25 Watts
Cutout Diameter:	/



SD-525

Woofer:	51/4"Injection Cone
Tweeter:	1" ALuminum DOME
Impedance:	8Ω
Sensitivity:	87dB
Frequency Response:	80Hz - 20kHz
Rated Power:	25 Watts
Cutout Diameter:	/



SD-625

Woofer:	6.5"Injection Cone
Tweeter:	1" ALuminum DOME
Impedance:	8Ω
Sensitivity:	88dB
Frequency Response:	70Hz - 20kHz
Rated Power:	30 Watts
Cutout Diameter:	/



DY-5504C

Woofer:	51/4"Injection Cone
Tweeter:	1" ALuminum DOME
Impedance:	8Ω
Sensitivity:	87dB
Frequency Response:	90Hz - 20kHz
Rated Power:	25 Watts
Cutout Diameter:	/



DY-6602A

Woofer:	6.5"Injection Cone
Tweeter:	1" ALuminum DOME
Impedance:	8Ω
Sensitivity:	87dB
Frequency Response:	85Hz - 20kHz
Rated Power:	25 Watts
Cutout Diameter:	/



DY-8801C

Woofer:	8"Injection Cone
Tweeter:	1" ALuminum DOME
Impedance:	8Ω
Sensitivity:	88dB
Frequency Response:	80Hz - 20kHz
Rated Power:	30 Watts
Cutout Diameter:	/



DY-5501B

Woofer:	51/4"Injection Cone
Tweeter:	1" ALuminum DOME
Impedance:	8Ω
Sensitivity:	87dB
Frequency Response:	90Hz - 20kHz
Rated Power:	25 Watts
Cutout Diameter:	/



DY-6503B

Woofer:	6.5"Injection Cone
Tweeter:	1" ALuminum DOME
Impedance:	8Ω
Sensitivity:	88dB
Frequency Response:	85Hz - 20kHz
Rated Power:	25 Watts
Cutout Diameter:	/